# Technical Data Sheet code 11431 **M 150/6'' AT**

Wall/window axial fans






| Certifications |       |  |
|----------------|-------|--|
| CE             | CE    |  |
| <b>())</b>     | ссс   |  |
| ERC            | EAC   |  |
| -e             | Mark  |  |
| UK<br>CA       | UKCA  |  |
| CB TEST CERTIF | ICATE |  |

## TECHNICAL AND PERFORMANCE DATA

| Frequency (Hz)              | 50   | Voltage (V)                       | 220-240 |
|-----------------------------|------|-----------------------------------|---------|
| Insulation class            | ll°  | Weight (Kg)                       | 1,1     |
| IP                          | Χ4   | Max airflow (l/s)                 | 93,1    |
| Max absorbed current (A)    | 0,15 | Max airflow (m³/h)                | 335     |
| Max absorbed power (W)      | 29   | Max pressure (mmH2O)              | 6       |
| Max ambient temperature for | 50   | Max pressure (Pa)                 | 59      |
| continuous operation (°C)   |      | RPM                               | 2100    |
| Nominal diameter (mm)       | 160  | Sound pressure Lp [dB (A)] at 3 m | 46      |
| Ø Discharge hole (mm)       | 156  |                                   |         |

### DIMENSIONS



| Size A (mm) | 214 |
|-------------|-----|
| Size B (mm) | 215 |
| Size C (mm) | 117 |
| Size D (mm) | 47  |
| Size E (mm) | Ø   |
|             | 156 |

### PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com

#### UNITED KINGDOM & REP. OF IRELAND Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com

# **Technical Data Sheet** CODE 11431 M 150/6" AT

Wall/window axial fans

## DESCRIPTION

• Material: UV resistant plastic (prevents ageing caused by exposure to sunlight).


Nominal diameter 150 mm.
Motor protected against thermal overload, with shaft turning in self-lubricating bushings, coupled to screw type thermoplastic impeller with wing profile blades.

• Maximum air flow: 335 m3/h.

• Equipped with electronic timer designed to shut off the motor automatically after a set interval, selectable during installation in the

range 3'-20' (default setting 3').
Equipped with system by which the louvres of the grille are opened and closed automatically.

### **CURVES**



### ACCESSORIES





S 150/6 Code 22156

F 150/6" Code 22133

#### PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com UNITED KINGDOM & REP. OF IRELAND Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com

